

780-2050nm Polarization beam Combiner/Splitter

Features

Low insertion
High return loss
High extinction ratio
High stability

Application


Fibre optic current sensor
Fiber Sensing & Fiber Lasers
Optical fiber gyro
Coherent telecommunication system

Specifications

Parameter		Unit	Value							
Rank			P	A	P	A	P	A	P	A
Central wavelength		nm	2050, 2000, 1950		1550, 1480, 1310		1064, 1030, 980		850, 808, 780	
Operating wavelength range		nm	±40		±40		±20		±10	
Typical insertion loss@23 °C		dB	0.6	0.8	0.4	0.5	0.6	0.7	0.6	0.7
Maximum insertion loss@23 °C		dB	1.0	1.2	0.6	0.7	0.8	0.9	0.8	0.9
Minimum extinction ratio@23 °C		dB	20	18	22	20	22	20	22	20
Minimum directivity		dB	50							
Minimum return loss		dB	50							
Maximum optical power(CW)		mW	300							
Maximum tensile load		N	5							
Fiber type	port1 & 2		PM Panda fiber							
	port 3		SM fiber or PM Panda fiber							
Operating temperature		°C	-5~+70							
Storage temperature		°C	-40~+85							

When using the Connector, the processing power is only 1W, the Insertion loss is 0.3dB higher, the return loss is 5dB lower, and the extinction ratio is 2dB lower. The Connector key is aligned with the slow axis.

Package dimensions



Ordering information

PBS/C-①①①①-②-③③③-④④④-⑤-⑥-⑦-⑧-⑨
①①①①: Wavelength ②: Type ③: Working axis

0698=T1064nm/R980nm P=Perfect grade 1=SM Fiber to PM Fiber
0698=T1064nm/R980nm A=A grade 2=PM Fiber to PM Fiber, Port 3
SSSS=Specify 3=PM Fiber to PM Fiber, Port 3

⑥: Package dimensions ⑦: Length ⑧: Pigtail type
0=φ5.5x35mm H=0.5m 1=250um bare fiber
S=Specify 1=1.0m 2=900um loose tube
S=Specify S=Specify

④④④: Port3 ⑤⑤⑤: Port1,2
Fiber type Fiber type
001=PM1550 001=PM1550
008=SMF-28E 003=PM980
SSS=Specify SSS=Specify

⑨: Connector
0=None
1=FC/UPC
2=FC/APC
S=Specify